



NOTES:

• STANDARD MAXIMUM SECTION SIZE OF GRATE/MAT WIDTH NOT TO EXCEED 10'-0" UNLESS OTHERWISE SPECIFIED

• FRAME ANCHOR SPACING: 6" FROM CORNERS, 24" MAX

• VERIFY TRAFFIC DIRECTION AND THAT SECTIONING DOES NOT OCCUR IN A TRAFFIC LANE

• ALL RAIL COMPONENTS ARE MADE OF 6063-T6 ALUMINUMALLOY, ALL FRAME COMPONENTS ARE MADE OF 6063-T5 ALUMINUM ALLOY (NOT ADDITIONAL OF MAIN APPLICACE MOUNT FEMALE)

APPLICABLE WITH VINYL SURFACE MOUNT FRAME) TREAD RAILS MUST RUN PERPENDICULAR TO TRAFFIC DIRECTION

• TRIM THE FILLER PROVIDED TO ENSURE A TIGHT FIT IN THE TRAFFIC DIRECTION (NOT APPLICABLE WITH VINYL SURFACE MOUNT FRAME)

* AVAILABLE IN ALTERNATING TREADS

DESCRIPTION:

MATdesign®, 3/8", Aluminum, Roll-up Mat with Cast In Place, Level Bed, Aluminum Frame

BMD38-FLBC

SCALE: NTS

F-3